

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number  
**WO 03/107086 A1**

(51) International Patent Classification<sup>7</sup>: **G02F 1/167,**  
1/1335

(21) International Application Number: **PCT/IB03/02321**

(22) International Filing Date: **27 May 2003 (27.05.2003)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
02077333.9 13 June 2002 (13.06.2002) **EP**

(71) Applicant (*for all designated States except US*): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];**  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **JOHNSON, Mark, T. [GB/NL];** c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **HENZEN, Alexander, V. [NL/NL];** c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **CORNELISEN, Hugo, J. [NL/NL];** c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **DEGUELLE, Wilhelmus, H., G.;** internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **IMPROVED ELECTRO-OPTICALLY ACTIVE DEVICE**



(57) Abstract: This invention relates to an electro-optically active display device, comprising at least one individually addressable pixel, each pixel being provided with an obstructing element(3), such as a reservoir light shield, a black matrix or a mirror element. According to the invention, a portion of at least one component is positioned beneath the obstructing element in such a way that the portion is not visible for a viewer of the display device.



WO 03/107086 A1

## Improved electro-optically active device

The present invention relates to an improved electro-optically active display.

An electrophoretic display, being one example of an electro-optically active display where there is physical transport of the electro-optically active medium through the device, essentially comprises a suspension of coloured particles in a liquid having another colour than the above particles. The display may be driven in two states, a distributed state, in which the particles are distributed in a display cell in such a way that they essentially cover the cell area, and a collected state, in which the particles are collected in a chosen area of the cell, in order to affect the transmission of the cell in a small extent, if any. For the collection of particles, some electrophoretic displays comprises a reservoir part incorporated in the cell. The reservoir part comprises an obstructing light shield element, behind which the particles may be collected in said collected state, in such a way that the particles are not visible for a viewer. This solution has the drawback that said obstructing light shield element takes up a part of the cell area, and thereby limits the transmission of the cell, but on the other hand, the remaining active transmission area of the cell may be totally emptied on particles in the collected state, thereby offering good transmission characteristics in this state.

However, usually an electrophoretic display further comprises of a regular lateral array of electrophoretic cells, said array being driven by means of active matrix driving. Such active matrix driving requires a large number of components, which must be placed in each of the pixel cells, making up the display. Examples of such components are spacers, gate and data lines, storage capacitors and TFTs. Since such components are placed in the cell, these will occupy a part of the active viewing and transmission area of the cell, thereby limiting the transmission of the cell. This is especially the case in electrophoretic transmissive or transfective displays, in which the electrophoretic layer is switched by lateral fields.

Hence, a problem with prior art displays is that a comparatively large area of the cell is occupied with a variety of components as stated above, which limits the transmission capabilities of the display.

Previously, some attempts have been made to solve the above problem, for example by making the components as small as possible or by making them essentially transparent, as suggested by US-6 337 761. However, the components may still have a negative effect on the transmission through the active cell area, and therefore an improved display device, overcoming the above drawback, is desired.

Hence, the object of the present invention is to overcome at least some of the drawbacks with the prior art electrophoretic displays, and provide a display with improved transmission characteristics.

The above and other objects are achieved by the invention by an electrophoretic display device, comprising at least one individually addressable pixel, each pixel being provided with an obstructing element, being characterised in that a portion of at least one component, being one of an electrical or a mechanical component, is positioned beneath the obstructing element in such a way that the portion is not visible for a viewer of the display device. In this way, the maximum area of an active cell area is available for transmissive operation, and hence the transmission of the display device is improved.

Examples of the obstructing element are reservoir light shield, black matrix and mirror element.

Preferably, said at least one component is one of a spacer, a barrier a gate electrode, a data electrode, a storage capacitor or a thin film transistor, which are all components commonly present in current electrophoretic displays. However, many other components such as sensors for temperature etc. may in accordance with the invention also be positioned in the same way to achieve the same advantageous effects.

According to a preferred embodiment of this invention, said display is a reservoir electrophoretic display device, comprising a reservoir light shield, beneath which one or more of an electrode, a storage capacitor and a thin film transistor is positioned. In this case, the light shield is necessarily present in the cell, and by positioning other components beneath said light shield, the active transmission area of the cell may be maximised.

Moreover, said pixel may further comprise a reflective element for enabling transfective operation, whereby a portion of an additional component, such as a source electrode is positioned beneath the reflective element, in such a way that it is not visible for a viewer of the display device. By covering source lines with the reflector, the area available for transmission is maximised, in the case of transfective operation.

This invention will hereinafter be described by means of presently preferred embodiments, with reference to accompanying drawings.

5 Fig 1 is a plan view of a possible array layout in accordance with this invention.

Fig 2 is schematic cross-section of a reservoir electrophoretic display device in accordance with the invention.

10 This invention relates to an electrophoretic display device 1, for example as shown in fig 2, comprising a plurality of cells, each cell 2 comprising a suspension of charged coloured particles in a light-transmissive fluid. Each cell 2 essentially comprises a transmissive front substrate 2, a gate electrode 5, a source electrode 4 and a back substrate, 15 being arranged to be reflective, transmissive or transfective (fig 2 shows a transfective device as an example). The arrangement of these components will be defined below. The cell further comprises a light shield element 3 in order to provide a reservoir part of the cell. The remaining part of the cell, not being covered by the light shield element 3, constitutes an active cell part. The display may be driven in two states, a collected state and a distributed 20 state. In the distributed state, the electrodes 4, 5 are so driven that the particles of the suspension are distributed throughout the active cell part, so that light being transmitted through the cell in either direction are disturbed by the presence of said particles. In the collected state, the electrodes 4, 5 are so driven that the charged particles essentially are collected in the reservoir part of the cell, and thereby do not disturb the transmission of light 25 through the active cell part. In order to achieve the desired characteristics of the light transmission in the distributed state, the pigmentation and colouring of the pigments and the light-transmissive fluid may be adjusted in accordance with prior art.

Fig 1 is a plan view of one possible embodiment of the invention. Fig 1 discloses a part of an electrophoretic display active matrix array 1, comprising four cells. 30 Each of said cells 2 is associated with a light shield 3 in order to provide a reservoir part of the cell. The display further comprises a source line 4 as well as a gate line 5. In accordance with the invention, the gate line 5 is positioned beneath the light shield 3, so that it is not visible for a viewer of the display. In this way, the gate line 5 do not occupy any extra space of the active cell part, and hence do not affect the transmission characteristics of the display.

The source line 4 is in a known manner positioned essentially perpendicular to the gate line 5. Furthermore, the display cell comprises a TFT 8 (thin film transistor) and a storage capacitor 6, the combination of which is used to apply selected voltages to each individual pixel, by means of an addressing scheme as is commonly used in liquid crystal displays (LCDs) in accordance with prior art. Both the TFT and the storage capacitor are positioned beneath the light shield 3, so that they are not visible for a viewer of the display and hence do not occupy any extra space of the active cell part. By organising the above components in this way, the maximum area is available for transmissive operation of the display. The above configuration may moreover be used in any one of a reflective, transmissive or transreflective display device. In the case of a transreflective device, in which a part of the back substrate of the cell is provided with reflective element 11, as described above, it is further possible to position said source line 4 beneath the reflector (i.e. not visible for a viewer of the display element), and thereby maximise the area available for transmission.

The above configuration is especially suitable in transreflective and transmissive electrophoretic displays using a lateral field in combination with the above reservoir function. Since the reservoir is an inactive area of the cell and shields everything in the affected area from view, essentially all electrical and mechanical components required for the display should preferably be placed behind said light shield defining the reservoir, thereby maximizing the transmission. Such components may for example include gate and source electrodes, TFTs, storage capacitors, spacers, barriers and sensors.

Alternatively, components of the above mentioned kind may be positioned behind other elements, such as under a black matrix or a mirror element, already present in the display structure.

Although this invention has been described with respect to specific embodiments, the details thereof are not to be construed as limitations, and many variations, modifications and alterations will be apparent for a man skilled in the art, and is intended to be included within the scope of this invention. As a specific example, the invention may not only be used in electrophoretic displays, but is equally applicable to other electro-optically active displays, which work on the principle that there is a physical transport of electro-optically active medium between a visible pixel area and a more or less hidden area. Other examples of such displays are electro-wetting displays, which utilise movement of coloured oil layers, and electro-mechanical displays, which utilise the movement of for example foils.

## CLAIMS:

1. Electro-optically active display device with physical transport of the electro-optically active medium through the device, comprising at least one individually addressable pixel, each pixel being provided with an obstructing element, characterised in that a portion of at least one component, being one of an electrical or a mechanical component, is positioned beneath the obstructing element in such a way that the portion is not visible for a viewer of the display device.

2. Display device according to claim 1, wherein said at least one component is one of a spacer, a barrier a gate electrode, a data electrode, a storage capacitor, a sensor or a thin film transistor.

3. Display device according to claim 1, wherein said display is a reservoir electrophoretic display device, comprising a reservoir light shield, beneath which one or more of an electrode, a storage capacitor, a sensor, and a thin film transistor is positioned.

4. Display device according to claim 3, said pixel further comprising a reflective element for enabling transreflective operation, whereby a portion an additional component, such as a source electrode is positioned beneath the reflective element, in such a way that the portion is not visible for a viewer of the display device.

5. Display device according to any one of the claims 1-2, wherein said display is one of an electrophoretic display, an electro-wetting display or an electro-mechanical display.

1/1




FIG. 1




FIG. 2

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP 03/02321

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G02F1/167 G02F1/1335

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No. |
|------------|--|-----------------------|
| X          | TOKO Y ET AL: "DISPLAY PERFORMANCES OF MOBILE FINE PARTICLE DISPLAY WITH LIQUID CRYSTAL"<br>2002 SID INTERNATIONAL SYMPOSIUM DIGEST OF TECHNICAL PAPERS. BOSTON, MA, MAY 21 - 23, 2002, SID INTERNATIONAL SYMPOSIUM DIGEST OF TECHNICAL PAPERS, SAN JOSE, CA: SID, US, vol. 33 / 1, 21 May 2002 (2002-05-21), pages 526-529, XP001134288 figures 1,2 | 1,5                   |
| A          | US 6 337 761 B1 (ROGERS JOHN A ET AL)<br>8 January 2002 (2002-01-08)<br>cited in the application<br>the whole document   | 1                     |

---  
-/--  
---

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

26 August 2003

Date of mailing of the international search report

18/09/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Gill, R



# INTERNATIONAL SEARCH REPORT

Internat Application No  
PCT/ID 03/02321

| C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT |   |                       |
|--|---|-----------------------|
| Category *   | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
| P,X  | EP 1 306 716 A (SEIKO EPSON CORP)<br>2 May 2003 (2003-05-02)<br>abstract<br>page 18, column 33, paragraph 174; figures<br>1,2,4 | 1,2,5                 |
| P,X  | WO 03 019279 A (KONINKL PHILIPS<br>ELECTRONICS NV) 6 March 2003 (2003-03-06)<br>page 5, line 10 - line 11; figure 3             | 1-3,5                 |

# INTERNATIONAL SEARCH REPORT

Internat Application No  
PCT/JP 03/02321

| Patent document<br>cited in search report |    | Publication<br>date | Patent family<br>member(s)  | Publication<br>date  |
|---|----|---------------------|---|--|
| US 6337761                                | B1 | 08-01-2002          | EP 1089118 A2<br>JP 2001159765 A  | 04-04-2001<br>12-06-2001   |
| EP 1306716                                | A  | 02-05-2003          | JP 2003177427 A<br>CN 1410805 A<br>EP 1306716 A2<br>JP 2003177428 A<br>US 2003076459 A1 | 27-06-2003<br>16-04-2003<br>02-05-2003<br>27-06-2003<br>24-04-2003 |
| WO 03019279                               | A  | 06-03-2003          | WO 03019279 A1<br>US 2003038772 A1  | 06-03-2003<br>27-02-2003   |